

SC0928E/SC1328E ELECTRIC SCISSOR LIFTS



PRODUCT HIGHLIGHTS



Reduced maintenance costs

- Lower cost of ownership with highly versatile parts and components
- Rapid, convenient transportation with forklift slots and lifting point
- Double-door design for easy maintenance



Efficient and environmentally friendly

- Higher work efficiency
- Environmental protection, zero emissions
- Folding guardrails for easy transport



Reliable performance

- Small turning radius, flexible operation
- Pothole protection system as standard



Standard configuration

| | | |
|-------------------------------|------------------------------|-----------------------------------|
| Proportional controls | Self-lock gate on platform | Unidirectional platform extension |
| Drivable at full height | Non-Marking Tires | DC motor drive |
| Automatic Braking System | Emergency Descent System | Emergency stop |
| Tubing Explosion-Proof System | Fault diagnosis system | Tilt protection system |
| All Motion Alarm | Horn | Safety brackets |
| Fork Lift pockets | Charging Protection System | Flashing beacon |
| Foldable Guard Rails | Automatic pothole protection | Overload sensor |

Optional configuration

| | | |
|--------------------------|-------------------------|--------------------------|
| AC power on the platform | Platform working lights | Air pipe to the platform |
|--------------------------|-------------------------|--------------------------|

SC0928E/SC1328E ELECTRIC SCISSOR LIFTS

| Dimensions | SC0928E (Indoors/Outdoors) | SC1328E (Indoors/Outdoors) |
|---|-----------------------------|-----------------------------|
| Maximum Working Height (Indoor) (A) | 18ft1in | 21ft4in |
| Maximum Platform Height (Indoor) (B) | 11ft6in | 14ft9in |
| Maximum Working Height (Outdoor) (A) | 18ft1in | 18ft1in |
| Maximum Platform Height (Outdoor) (B) | 11ft6in | 11ft6in |
| Overall Length (C) | 4ft12in | 4ft12in |
| Overall Width (D) | 2ft6in | 2ft6in |
| Overall Height (Rails up) (E) | 6ft3in | 6ft6in |
| Overall Height (Rails down) | 5ft | 5ft3in |
| Platform Dimensions (Length/Width) (H) (F) | 54x29in | 54x29in |
| Maximum horizontal extension (G) | 2ft | 2ft |
| Minimum Ground Clearance (Stowed) | 2.1in | 2.1in |
| Minimum Ground Clearance (Raised) | 0.6in | 0.6in |
| Wheel Base | 3ft8in | 3ft8in |
| Performance | | |
| Platform Allowable Occupants (Indoors/Outdoors) | 2/1 | 2/1 |
| S.W.L. | 530lbs | 530lbs |
| S.W.L. On Extension | 249lbs | 249lbs |
| Travel Speed (Stowed) | ≥2.5mph | ≥2.5mph |
| Travel Speed (Raised) | ≥0.5mph | ≥0.5mph |
| Up/Down Time | 20/22sec | 25/27sec |
| Maximum Gradeability | 25% | 25% |
| Minimum Turning Radius | 4ft5in | 4ft5in |
| Maximum Working Slope | 1.5°/3° | 1.5°/3° |
| Tire | Φ10x3in | Φ10x3in |
| Power | | |
| Batteries | 24V100Ah/3HR | 24V100Ah/3HR |
| Integrated Charger | 24V/15A | 24V/15A |
| Drive Mode | Electric motor, front-wheel | Electric motor, front-wheel |
| Lifting Motor | 24V DC/1.3kw | 24V DC/1.3kw |
| Drive Motor | 2x24V DC/0.4kw | 2x24V DC/0.4kw |
| Weight | | |
| Overall Weight | 2030lbs | 2120lbs |

We reserve the right to make specification changes without notification.

All information is subject to change to reflect ongoing improvements. 202508.

